

E04866

TECHNICAL DATASHEET

INDUSTRIAL 4G/5G RUGGED MODEM



The Industrial 4G/5G Rugged modem is Ambra Solutions' feature filled wireless device to meet your ethernet over 4G/5G connectivity requirements. It provides the data bandwidth for your data intensive solutions as well as integrating other functionalities, such as multiple I/O, CAN bus, Ignition input, BLE and GPS. These functionalities which make it one of the most flexible devices on the market as well as making it compatible with Ambra Solutions' proprietary iPS tracking solution for fleet and asset geo tracking capabilities.

FEATURES AND BENEFITS

- Rugged Enclosure for industrial, outdoor harsh environment and mining applications
- 4G / 5G modem
- iPS ready for asset tracking indoor and outdoor
- Linux Based Open WRT OS
- Layer 2 tunneling
- Web UI for device configuration and management

Frequency Bands

Model	E04866
Category	5G NR & LTE CAT20
GNSS Support	GPS, GLONASS, Galileo, BeiDou, QZSS
Supported bands	5G FR1 bands : n1, n2, n3, n5, n7, n8, n20, n25, n28, n30, n38, n40, n41, n48, n66, n71, n75, n77, n78, n79 SA + NSA default off – n12, n13, n14, n18, n26, n29, n48, n75, n76 LTE bands : B1, B2(B25), B3, B4(B66), B26(B5, B18, B19), B7, B8, B12(B17), B13, B14, B20, B28, B29(DL), B30, B32(DL), B34, B38, B39, B40, B41, B42, B43, B46(LAA), B48(CBRS), B66, B71

Product Pinout

J1 (PWR+CAN) - M12-5 Series	<ul style="list-style-type: none"> - Power + / 8VDC to 60VDC; OVP 200VDC - Input Voltage Reverse and Transient Protection; Typical operating power 11W @25C - IGN (Ignition) input - Power - / Battery GND - CAN Lo / Either CAN (250, 500, 1000) - Can Hi / Either CAN 	Ethernet - ETH1	10BASE-T, 100BASE-TX or 1000BASE-T M-12 X-Coded connector
J2 GPIO	The J2/GPIO connector can be ordred in various I/O configuration : <ul style="list-style-type: none"> - RS232 @TTL 3V3 - M12 A-Coded 8 positions connector 	Ethernet - ETH2	10BASE-T, 100BASE-TX or 1000BASE-T Ethernet Port Passive PoE Input Voltage Range 10 to 60V M-12 X-Coded connector
RF Connectors	Antenna 1-2-3-4 : N-Type	Bluetooth - N-Type	Ethernet - ETH3-4
		GPS - TNC	
			10BASE-T, 100BASE-TX or 1000BASE-T Ethernet Port 802.3at PoE+ Input Voltage Range 37 to 57V M-12 X-Coded connector

Specifications and Sensors

Environmental	Mechanical	Sensors
Operating Temperature	-40°C to 70°C	Case Material
Storage Temperature	-40°C to 85°C	Aluminium blue anodized
Ingress Protection	IP67	Dimensions
EMC	IEC/EN 61000-6-3	160mm x 215mm
		Weight
		2,7 lbs
		Temperature monitor
		Voltage monitor
		Gyroscope
		Magnetometer
		Accelerometer
		Pressure sensor

Ordering Information

CAT Type	4 Ethernet ports
CAT20 (4G + 5G)	E04866-04-00-05-ES (4G)
	E04866-04-01-05-ES (4G + Wifi)
	E04866-05-00-05-ES (5G)
	E04866-05-01-05-ES (5G + Wifi)

sales@ambra.co

1-877-374-3997

www.ambra.co