




# AMBRA SOLUTIONS SUITCASE LTE CAMERA

This Suitcase include a PTZ dome camera with a high-resolution 1080p60 HD sensor and a 12x optical zoom that allows operators to monitor wide scenes without losing any details. The camera's aesthetic design and flexible mounting options allow unobtrusive surveillance of large halls, reception areas, or waiting areas that would otherwise require multiple cameras for effective surveillance. Also, pan and tilt preset repeatability are accurate to within ±0.1 degrees to ensure that the correct scene is captured every time.

### FEATURES AND BENEFITS

- Indoor / Outdoor
- Design for mining application
- Plug & Play installation
- Maximum pan speed of 160 degrees per second
- Maximum tilt speed of 120 degrees per second

## MECHANICAL SPECIFICATIONS      ELECTRICAL SPECIFICATIONS

<b>Pan/Tilt Modes</b>	Normal: 0.1°/s - 120°/s Turbo: Pan: 0.1°/s - 160°/s; Tilt: 0.1°/s 120°/s	<b>Input voltage</b>	18 – 58 VDC, Connection from Amba LTE Network
<b>Pre-position Speed</b>	Pan: 160°/s Tilt: 120°/s	<b>Power consumption</b>	2 W
<b>Pan Range</b>	360° continuous		
<b>Tilt Angle</b>	-90° to 0°		
<b>Pre-position Accuracy</b>	± 0.1° typ		
<b>Pre-positions</b>	256		

## TECHNICAL SPECIFICATIONS      NETWORK

<b>Imager</b>	1/2.8" progressive scan CMOS	<b>Video compression</b>	H.265 / H.264 / M-JPEG
<b>Effective Picture Elements</b>	1945 x 1097 (2.13 MP)	<b>Frame rate</b>	60fps at all resolutions
<b>Lens Focal Length</b>	12x Zoom 5.3 mm to 64 mm (F1.6 to F2.8)	<b>Resolution</b>	1080p / 720p / D1 4:3 (cropped) / SD (432p, 288p)
<b>Field of View (FOV)</b>	4.9° to 58.5°	<b>IP delay (typical)</b>	60 fps: 200 ms
<b>Focus</b>	Automatic with manual override	<b>Ethernet</b>	10/100BASE-T
		<b>Encryption</b>	TLS 1.0, SSL, DES, 3DES, AES
		<b>Protocols</b>	IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/ RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, ARP, DHCP, APIPA (Auto-IP, link local address), NTP (SNTP), SNMP (V1, V3, MIB-II), 802.1x, DNS, DNSv6, DDNS (DynDNS.org, selfHOST.de, no-ip.com), SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox™, CHAP, digest authentication

## ORDERING INFORMATION      ENVIRONMENTAL

<b>Product Part Number / Description</b>	<b>Ingress Protection Rating/Standard</b>	IP51
M01060-PWR1 / LTE Modem and Camera Combined Suitcase, option -48Vdc	<b>Storage Temperature</b>	-40 °C to +60 °C (-40 °F to +140 °F)
M01060-PWR2 / LTE Modem and Camera Combined Suitcase, option 120Vac, -48Vdc	<b>Operation Temperature</b>	-10 °C to +55 °C (+14 °F to +131 °F)
	<b>Humidity</b>	Up to 90% RH, non-condensing